

| | |
|-------------------|-------------|
| Applicant's Name: | Consent No: |
| Property Address: | Pool No.: |

ITEMS TO BE CHECKED [Checked against the approved Building Consent (BC) documents]

Key:
Decision: ☐ or ☐ = Pass ☐ or ☐ = Fail, further inspection required ☐ or ☐ or ☐ = Not Applicable
Reason for decision: Compliance or non compliance with the approved building consent documents

NOTE: Portable Pools: Portable pools are treated in the same way as other residential pools. They must have barriers that restrict access by young children if they are filled or partly filled with water. Portable pools with a maximum depth of water of less than 400mm are exempt.

OTHER RESIDENTIAL POOL ☐ Not applicable (Schedule FSA1987, Building Act 2004)

POOL AREA

- ☐ No vegetable garden
- ☐ No clothes line
- ☐ No children's sand-pits, stand-alone slides, swings, garden sheds etc.
- ☐ No pet doors to immediate pool area

FENCE HEIGHT- the fence shall extend:

- ☐ At least 1.2 m above the ground on the outside of the fence
- ☐ At least 1.2 m above any permanent projection or object permanently placed on the ground outside and within 1.2 m of the fence
- ☐ Where perforated fencing material has openings greater than 10mm in diameter and less than 50mm, the fence height must be no less than 1.8 m above the ground / projection / object.
- ☐ Where perforated fencing material has openings less than 10mm, fence height can be reduced to 1.2 m above the ground / projection / object.

GROUND CLEARANCE

- ☐ Any clearance between the bottom of the fence / gate and ground / permanent projection shall not exceed 100 mm

GATES AND DOORS

- ☐ Gates and doors cannot open inwards towards the immediate pool area.
- ☐ Gates and doors must be clear of any obstruction that could hold them open. No other means of holding the gate or door open is provided
- ☐ When lifted up or pulled down a gate or door it does not release the latching device or come off its hinges or provide a ground clearance greater than 100 mm

FENCING MATERIALS see FSP Act 1987

- ☐ All materials / components are durable and erected so as to inhibit any child less than 6 years from climbing over or crawling under the fence from the outside.

- ☐ The spacing between adjacent vertical pales, panels, or posts does not exceed 100 mm at any point.
- ☐ All non-vertical fencing supports, rails, rods, and wires, and bracing are inaccessible for climbing from the outside of the pool enclosure at time of inspection.
- ☐ All non-vertical fencing supports, rails, rods, and wires, and bracing on the outside of the fence are NO less than 900 mm apart, and the vertical boards do not exceed 10 mm apart at any point. There are no other horizontal elements between these two supports, rails, rods, and wires, or bracings at any point.
- ☐ Perforated fencing material: openings must not be greater than 50 mm in diameter.
- ☐ All perforated fencing materials are firmly attached to a supporting structure or otherwise constructed to prevent access of children under the age of 6 years

OPERATION OF GATES AND DOORS

Latching device accessibility:

- ☐ Every gate or door leading to the immediate pool area shall be fitted with a latching device
- ☐ Where the latching device is accessible from the outside of the fence only by reaching:
 - over the fence / gate or door, or
 - through a hole in the fence / gate / door;
 - the latching device and the lowest point of any hole giving access to it, shall be at least 1.2 metres above the ground on the outside of the fence

Height of latching device:

- ☐ Where the latching device is otherwise accessible from the outside of the fence / gate / door, the latching device shall be at least 1.5 m above the ground on the outside of fence

Pool No.:

Self-closing:

- ☐ Every gate / door shall be fitted with a device that will automatically return the gate / door to the closed position; and operate the latching device when the gate / door is stationary and 150 mm from the closed position

WINDOWS IN BUILDING WALLS

☐ Not applicable

- ☐ All windows within 1200 mm of the floor / permanent object are fitted with a window restrictor stay, restricting the opening to 100 mm or are fitted with a latching device at least 1500 mm from the floor / permanent object

☐ Not applicable

- ☐ Compliance with these clauses is impossible, unreasonable or in breach of another Act, regulation or bylaw; and (Note: visual impact is not accepted by MBIE as a reason for non-compliance, pg 20 & 22 Guidelines to FSA for TAs)
- ☐ The door is fitted with a lock that, when properly operated, prevents the door from being readily opened by children under the age of 6 years

☐ Not applicable

- ☐ Side walls of the pool are > 1.2 m above the adjacent ground level or any permanent projection from or object standing on the ground
- ☐ The outside surface of the pool's side walls is constructed so as to inhibit climbing
- ☐ Any means of access to the interior of the swimming pool can be readily removed or rendered inoperable, and is removed or rendered inoperable when the pool is not in use.

☐ Photos attached (*if relevant*) ☐ Memo / Instruction No: ☐ Verbal instruction (*specify*):

Pool complies:

- Officer Name:

Signature:

Date:

Pool complies:

- Officer Name:

Signature:

Date:

